

## Water Hand Portable Fire Extinguishers

### Features

- Meets or exceeds UL requirements
- Simple operation and maintenance
- Squeeze grip, positive on-off operation
- Brass chrome plated valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

### Description

The SENTRY Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a stainless shell and chrome plated valve. The nameplate features easy to read step-by-step instructions for operating the extinguisher. The Schrader valve allows for easy recharge in the field. Use of fresh, clean water is recommended. Reference Manual Part No. 429442, latest revision.

### Specifications

Model No.:	W02-1
UL Rating:	2-A
Capacity:	2.5 gal (9.5 L)
Extinguisher Height:	25.5 in. (648 mm)
Width:	9 in. (229 mm)
Depth:	7 in. (178 mm)
Range:	35 ft (10.7 m)
Discharge Time:	Approximately 50 seconds
Bracket:	Wall mount
Temperature:	+40 °F to 120 °F (4.5 °C to 48.9 °C)



006492

### Ordering Information

Part No.	Description	Approximate Shipping Weight
430847	SENTRY Model W02-1 Pressurized Water-Type Fire Extinguisher 2.5 gal (9.5 L)	9.0 lb (4.1 kg)

**Note:** The converted values in this document are provided for dimensional reference only and do not reflect an actual measurement.

SENTRY and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.