

Data/ Specification Sheet

PYRO-CHEM Carbon Dioxide Hand Portable Fire Extinguishers

FEATURES

- UL/ULC Listed
- Simple, trouble-free operation and maintenance
- Features upright positive on-off operation utilizing squeeze-grip activation
- Non-corrosive, non-conductive, clean extinguishing agent leaves no residue
- Aluminum models are available in 5, 10, 15 and 20 lb sizes (2.3, 4.5, 6.8, 9.1 kg)
- Strong, impact-resistant discharge horn
- One person operation
- Suitable for use in temperatures from -22 °F to 120 °F (-30 °C to 49 °C)
- Six-year limited warranty

APPLICATION

PYRO-CHEM Carbon Dioxide Fire Extinguishers are designed to protect areas where Class B (flammable liquids and gases) or Class C (energized electrical equipment) fires could occur. They may be used indoors where winds and drafts do not affect discharge or where a clean extinguishing agent is required.

Typical applications include:

- Laboratories
- Electronic equipment
- Low voltage electrical equipment
- Municipal fire departments



PART NO.	MODEL	UL RATING	EFFECTIVE RANGE	CAPACITY	DISCHARGE TIME	DIAMETER	WIDTH	HEIGHT
552083* 552087**	CO2-050-I PC CD05A-1	5-B:C	6 ft (1.8 m)	5 lb (2.3 kg)	10-12 seconds	5.3 in. (13.5 cm)	7.25 in. (18.4 cm)	19 in. (48.3 cm)
552084* 552088**	CO2-10-I PC CD10A-1	10-B:C	6 ft (1.8 m)	10 lb (4.5 kg)	10-12 seconds	7.0 in. (17.8 cm)	10.9 in. (27.8 cm)	21.25 in. (54 cm)
552085* 552089**	CO2-15-I PC CD15A-1	10-B:C	6 ft (1.8 m)	15 lb (6.8 kg)	13-15 seconds	7.0 in. (17.8 cm)	10.9 in. (27.8 cm)	28 in. (71.1 cm)
552086* 552090**	CO2-20-I PC CD20A-1	10-B:C	6 ft (1.8 m)	20 lb (9.1 kg)	15-17 seconds	8.1 in. (20.6 cm)	12 in. (30.5 cm)	28 in. (71.1 cm)

*Underwriters Laboratories Inc. Listed and USCG Approved

**Underwriters Laboratories of Canada Listed

CLASS **B** **C** FIRES



A Tyco International Company

Tyco Fire Protection Products
One Stanton Street
Marinette, WI 54143

Copyright © 2011 Tyco Fire Protection Products.
All rights reserved.