

# Data/ Specification Sheet

**CD-50-D-1 AND CD-100-D-1  
CARBON DIOXIDE  
WHEELED EXTINGUISHERS  
50 LB (23 KG) AND 100 LB (45 KG)**



007380

## FEATURES

- Simple operation and maintenance
- Portable, compact design
- Non-corrosive, non-conductive, clean extinguishing agent
- Available in 50 lb (23 kg) and 100 lb (45 kg) models
- UL listing
- One person operation
- Large 16 in (41 cm) semi-pneumatic rubber wheels

## DESCRIPTION

- Upright positive on-off operation utilizing the squeeze grip activation, precision machined, chrome plated, forged valves, TC approved steel cylinder mounted to a wheeled carriage for ease of mobility.
- Nameplate is made of aluminum and contains hazard identification as well as operating and maintenance instructions.
- Units are equipped with rubber-jacketed, wire-braided, high-pressure discharge hose.
- Hose and horn keep static electricity to a minimum.
- Suitable for use in temperatures from -40 °F to 120 °F (-40 °C to 49 °C).
- Carbon dioxide is a non-corrosive extinguishing agent that leaves no residue after a fire. As a gas, CO<sub>2</sub> provides its own pressure for discharge and will penetrate all parts of a hazard

PART NO.	MODEL	EFFECTIVE RANGE	CAPACITY	UL RATING	DISCHARGE TIME	DISCH. HOSE LENGTH	DEPTH	WIDTH	HEIGHT	WEIGHT
552333	CD-50-D-1	10-12 ft (3.1-3.7 m)	50 lb (22.7 kg)	20-B:C	35 seconds	15 ft (4.6 m)	28 in (71 cm)	20 in (51 cm)	58 3/4 in (1.5 m)	235 lb (106.6 kg)
552300	CD-100-D-1	10-12 ft (3.1-3.7 m)	100 lb (45.4 kg)	20-B:C	70 seconds	40 ft (12.2 m)	28 in (71 cm)	29 in (74 cm)	57 in (1.45 m)	400 lb (181.4 kg)

FIRE SUPPRESSION CAPACITY	CD-50-D-1	CD-100-D-1
Novice Operator	20 sq ft (1.9 sq m)	20 sq ft (1.9 sq m)
Experienced Operator	50 sq ft (4.7 sq m)	50 sq ft (4.7 sq m)

**CLASS B C FIRES**



PYRO-CHEM  
One Stanton Street  
Marinette, WI 54143-2542  
715-732-3465  
www.pyrochem.com

PYRO-CHEM is a trademark of Tyco International Ltd. or its affiliates.