

Pressurized Water Extinguisher

Features

- Meets or exceeds UL/ULC requirements
- Simple operation and maintenance
- Squeeze grip, positive on-off operation
- Brass chrome plated valve
- Waterproof stainless steel gauge
- Stainless steel shell
- Schrader valve for pressurization
- Easy service construction

Description

The PYRO-CHEM Stainless Steel Water Extinguisher can be utilized in many Class A hazards such as office environments and industrial locations, as well as warehouse and oxidizing chemical storage areas. The unit features a polished stainless steel shell and brass chrome-plated valve. The barcoded and bilingual nameplate features easy-to-read step-by-step instructions for operating the extinguisher. The Schrader valve allows for easy recharge in the field. Use of fresh, clean water is recommended. Refer to PYRO-CHEM Technical Manual Part No. 552056.

Specifications

Model No.:	PWS-25G
UL/ULC Rating:	2-A
Capacity:	2.5 gal (9.5 L)
Extinguisher Height:	25.5 in. (648 mm)
Width:	9 in. (229 mm)
Depth:	7 in. (178 mm)
Range:	35 ft (107 m)
Discharge Time:	Approximately 50 seconds
Bracket:	Wall mount
Temperature:	40 °F to 120 °F (5 °C to 49 °C)



UL EXTINGUISHER
(Part No. 552050) 008136



ULC EXTINGUISHER
(Part No. 552501) 008137

Ordering Information

Part No.	Description	Approximate Shipping Weight
552050	PYRO-CHEM Model PWS-25G Pressurized Water Fire Extinguisher, UL, 2.5 gal (9.5 L)	9.0 lb (4.1 kg)
552501	PYRO-CHEM Model PWS-25G Pressurized Water Fire Extinguisher, ULC, 2.5 gal (9.5 L)	9.0 lb (4.1 kg)

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

PYRO-CHEM and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.